

TECHNICAL DATA

ACCESS 200 36V/300A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	AU3761
Model	ACCESS 200
Туре	36V/300A
MAINS DATA (50/60HZ)	
Output Voltage [V]	36
Output Current [A]	300
Number of phases	3
Rated Voltage range [V]	380-415
Current at nominal voltage [A]	21.7
Recommended supply fuse [A]	25
Supply cable area	4x4 mm2
Supply cable length [m]	3
Typical Supply Connector	CEE32
Output cable cross-section	4/0 AWG
BATTERY CONNECTION	
Output cable cross-section	4/0 AWG
Output cable terminals (in unit)	M10
Output cable length [m]	3
Typical Output connector	DIN320
Output Voltage [V]	36
ELECTRIC DATA	
Standby Power Consumption [W]	<15
Power Consumption [W]	14283
Apparent Power Consumption [VA]	15034

Power Factor	0.95
Inrush current, do not tripp fuse of class [A]	В
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	92
PROPERTIES	
Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	A22
Certifications	CE
НМІ	LED / Display
HMI Language	SV / EN / ES / PT / DE
Reporting	Yes
Radio Communication	No
Charging Curve Set	Yes
I/O-cards	Multiple
CE	Yes
UL	No
CHARGING TIMES	
6 Hours cap.ah/5h	
8 Hours cap.ah/5h	1723
10 Hours cap.ah/5h	2500
12 Hours cap.ah/5h	3337
CHARGER DIMENSIONS	
Weight excl. cables [kg]	35
Weight incl. cables [kg]	44
Outer Dimensions Height [mm]	659

Outer Dimensions Width [mm]	256
Outer Dimensions Depth [mm]	459
Min Spacing Required	Se User Manual
SHIPPING DIMENSIONS	
Shipping Weight [kg]	47
Box Height [mm]	435
Box Width [mm]	370
Box Depth [mm]	690
CHARGING	
Charging Ionic	LK10-18 Ionic mixture
Charging Ionic Charging Standard	LK10-18 Ionic mixture LK10-06 Standard Curve
Charging Standard	LK10-06 Standard Curve
Charging Standard Charging Gel	LK10-06 Standard Curve LK20-09
Charging Standard Charging Gel Charging Li-Ion	LK10-06 Standard Curve LK20-09 O
Charging Standard Charging Gel Charging Li-lon Charging AGM	LK10-06 Standard Curve LK20-09 0 LK20-09
Charging Standard Charging Gel Charging Li-Ion Charging AGM Moisture Resistance	LK10-06 Standard Curve LK20-09 0 LK20-09 No
Charging Standard Charging Gel Charging Li-Ion Charging AGM Moisture Resistance Dusty Environment	LK10-06 Standard Curve LK20-09 0 LK20-09 No No

3 (3)

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.