

TECHNICAL DATA

ACCESS 200 48V/260A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD		
Family	ACCESS 200	
DC Rating	48V/260A	
Part number	AU4724	
Model code	1AA8512	
Part status	Released	
SUPPLY		
Number of phases	3	
Rated Voltage range [V]	440-440	
Nominal Voltage [V]	440	
Rated frequency [Hz]	50-60	
Current at nominal voltage [A]	22,5	
Current at min rated voltage [A]	22,5	
Current at max rated voltage [A]	22,5	
Recommended supply fuse class	C	
Recommended RCCB class	В	
Supply cable area	4x4 mm2	
Supply cable length [m]	?2,5	
Typical Supply Connector	CEE32	
Standby Power Consumption [W]	<15	
Power Consumption [W]	16249	
Apparent Power Consumption [VA]	17104	
Power Factor	0,95	
Leakage current [mA]	<3,5	
Efficiency (at rated power and no cables) [%]	93	

Printout date: 2025-12-01

OUTPUT DATA	
Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	48
Output Current [A]	260
Output cable cross-section	95 mm2
Output cable length [m]	3
Output cable terminals (in unit)	M10
Typical Output connector	DIN320
Output fuse, rating [A/VDC]	2x150A/150VDC
Output fuse type	Fast Semiconductor fuse
PROPERTIES	
Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	A22
Certifications	CE
Cloud connection	Yes
User interface	LED/Display
Charging Curve Set	Multiple Lead
I/O-cards	Optional
Reporting	Yes
Radio communication	Yes
CHARGER DIMENSIONS	
Weight excl. cables [kg]	34
Charger dimensions [mm]	659x256x459

SHIPPING DIMENSIONS

Box dimensions [mm]	435x370x690
Shipping Weight [kg]	45