

## **TECHNICAL DATA**

## ACCESS 200 80V/200A BATTERY CHARGERS

## STATED DATA ACCORDING TO MICROPOWER STANDARD

| Part number                      | MA6627       |
|----------------------------------|--------------|
| Model                            | ACCESS 200   |
| Туре                             | 80V/200A     |
| MAINS DATA (50/60HZ)             |              |
| Output Voltage [V]               | 80           |
| Output Current [A]               | 200          |
| Number of phases                 | 3            |
| Rated Voltage range [V]          | 600-600      |
| Current at nominal voltage [A]   | 21,1         |
| Recommended supply fuse [A]      | 25           |
| Supply cable area                | 4xAWG10      |
| Supply cable length [m]          | 3            |
| Typical Supply Connector         | Not included |
| Output cable cross-section       | 2xAWG2/0     |
| BATTERY CONNECTION               |              |
| Output cable cross-section       | 2xAWG2/0     |
| Output cable terminals (in unit) | M10          |
| Output cable length [m]          | 3            |
| Typical Output connector         | User defined |
| Output Voltage [V]               | 80           |
| ELECTRIC DATA                    |              |
| Standby Power Consumption [W]    | <10          |
| Power Consumption [W]            | 20817        |
| Apparent Power Consumption [VA]  | 21913        |

| Power Factor   | 0,95                   |
|--|------------------------|
| Inrush current, do not tripp fuse of class [A]           | Negligible             |
| Output Ripple  | <1                     |
| Efficiency (at rated power and no cables) [%]            | 93                     |
| PROPERTIES   |                        |
| Ingress protection                                       | IP20                   |
| Ambient temperature range (at full output power) [deg C] | -5 to +40              |
| Ambient max temp (with reduced output power) [deg C]     | 50                     |
| Cooling  | Fan                    |
| Short Circuit Protection                                 | 1                      |
| Wrong Polarity Protection                                | Fuse                   |
| Cabinet Type   | Α7                     |
| Certifications   |                        |
| НМІ  | LED / Display          |
| HMI Language   | SV / EN / ES / PT / DE |
| Reporting  | Yes                    |
| Radio Communication                                      | No                     |
| Charging Curve Set                                       | Yes                    |
| I/O-cards  | Multiple               |
| CE   | No                     |
| UL   | Yes                    |
| CHARGING TIMES   |                        |
| 6 Hours cap.ah/5h  |                        |
| 8 Hours cap.ah/5h  | 1149                   |
| 10 Hours cap.ah/5h                                       | 1665                   |
| 12 Hours cap.ah/5h                                       | 2221                   |
| CHARGER DIMENSIONS                                       |                        |
| Weight excl. cables [kg]                                 |                        |
| Weight incl. cables [kg]                                 |                        |
| Outer Dimensions Height [mm]                             | 659                    |
|  |                        |

| Outer Dimensions Width [mm]   | 256  |
|---|--|
| Outer Dimensions Depth [mm]   | 445  |
| Min Spacing Required  | 300  |
| SHIPPING DIMENSIONS   |  |
| Shipping Weight [kg]  | 44   |
| Box Height [mm]   | 560  |
| Box Width [mm]  | 360  |
| Box Depth [mm]  | 820  |
| CHARGING  |  |
| Charging Ionic  | LK10-18 Ionic mixture  |
|   |  |
| Charging Standard   | LK10-06 Standard Curve   |
|   |  |
| Charging Standard   | LK10-06 Standard Curve   |
| Charging Standard<br>Charging Gel   | LK10-06 Standard Curve<br>LK20-09  |
| Charging Standard<br>Charging Gel<br>Charging Li-Ion  | LK10-06 Standard Curve<br>LK20-09<br>O   |
| Charging Standard Charging Gel Charging Li-Ion Charging AGM   | LK10-06 Standard Curve           LK20-09           0           LK20-09   |
| Charging Standard         Charging Gel         Charging Li-Ion         Charging AGM         Moisture Resistance                           | LK10-06 Standard Curve           LK20-09           0           LK20-09           LK20-09           No              |
| Charging Standard         Charging Gel         Charging Li-Ion         Charging AGM         Moisture Resistance         Dusty Environment | LK10-06 Standard Curve           LK20-09           0           LK20-09           LK20-09           No           No |

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.