

TECHNICAL DATA

SHARP 100 80V/40A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STA	NDARD
Part number	SR6301
Model	SHARP 100
Туре	80V/40A
MAINS DATA (50/60HZ)	
Output Voltage [V]	80
Output Current [A]	40
Number of phases	3
Rated Voltage range [V]	380-415
Current at nominal voltage [A]	6.3
Recommended supply fuse [A]	10
Supply cable area	4x1,5 mm2
Supply cable length [m]	3
Typical Supply Connector	CEE16
Output cable cross-section	10 mm2
BATTERY CONNECTION	
Output cable cross-section	10 mm2
Output cable terminals (in unit)	M8
Output cable length [m]	3
Typical Output connector	DIN80
Output Voltage [V]	80
ELECTRIC DATA	
Standby Power Consumption [W]	<10
Power Consumption [W]	4112
Apparent Power Consumption [VA]	4329

Printout date: 2025-12-01

Power Factor	0.95
Inrush current, do not tripp fuse of class [A]	В
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	94
PROPERTIES	
Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	
Cabinet Type	S17
Certifications	CE
НМІ	
HMI Language	
Reporting	No
Radio Communication	No
Charging Curve Set	
1/O-cards	
CE	Yes
UL	No
CHARGING TIMES	
6 Hours cap.ah/5h	
8 Hours cap.ah/5h	
10 Hours cap.ah/5h	
12 Hours cap.ah/5h	
CHARGER DIMENSIONS	
Weight excl. cables [kg]	14
Weight incl. cables [kg]	16
Outer Dimensions Height [mm]	417

Outer Dimensions Width [mm]	256
Outer Dimensions Depth [mm]	243
Min Spacing Required	Se User Manual
SHIPPING DIMENSIONS	
Shipping Weight [kg]	18
Box Height [mm]	465
Box Width [mm]	365
Box Depth [mm]	525
CHARGING	
Charging Ionic	
Charging Standard	
Charging Gel	
Charging Li-lon	
Charging AGM	
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No