

## TECHNICAL DATA

# LION 200 80V/115A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	LION 200
DC Rating	80V/115A
Part number	LU6453
Model code	1AA8517
Part status	Released

### SUPPLY

Number of phases	3
Rated Voltage range [V]	230-240
Nominal Voltage [V]	230
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	31.6
Current at min rated voltage [A]	31.6
Current at max rated voltage [A]	30.2
Recommended supply fuse class	B
Recommended RCCB class	A
Supply cable area	4x10 mm <sup>2</sup>
Supply cable length [m]	3
Typical Supply Connector	GEE32
Standby Power Consumption [W]	<15
Power Consumption [W]	11928
Apparent Power Consumption [VA]	12556
Power Factor	0,95
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	93

## OUTPUT DATA

Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	80
Output Current [A]	115
Output cable cross-section	35 mm <sup>2</sup>
Output cable length [m]	3
Output cable terminals (in unit)	M10
Typical Output connector	DIN160
Output fuse, rating [A/VDC]	2x80A/150VDC
Output fuse type	Fast Semiconductor fuse

## PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	A22
Certifications	CE
Cloud connection	Yes
User interface	LED / Display
Charging Curve Set	Litium Alg or CAN
I/O-cards	CAN Included
Reporting	Yes
Radio communication	Yes

## CHARGER DIMENSIONS

Weight excl. cables [kg]	34.5
Charger dimensions [mm]	659x256x459

## SHIPPING DIMENSIONS

Box dimensions [mm]	435x370x690
Shipping Weight [kg]	42.4

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.*