

## TECHNICAL DATA

# MICROPOWER SQ30 PB 24V/100A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	Micropower SQ30
DC Rating	24V/100A
Part number	SN2429
Model code	1AB6451
Part status	Released

### SUPPLY

Number of phases	3
Rated Voltage range [V]	380-440
Nominal Voltage [V]	400
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	4.8
Current at min rated voltage [A]	5.1
Current at max rated voltage [A]	4.4
Recommended supply fuse class	C
Recommended RCCB class	A
Supply cable area	4x1,5 mm <sup>2</sup>
Supply cable length [m]	3
Typical Supply Connector	GEE16
Standby Power Consumption [W]	<5
Power Consumption [W]	3185
Apparent Power Consumption [VA]	3352
Power Factor	0.95
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	92

## OUTPUT DATA

Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	24
Output Current [A]	100
Output cable cross-section	35 mm <sup>2</sup>
Output cable length [m]	3
Output cable terminals (in unit)	M6
Typical Output connector	DIN160
Output fuse, rating [A/VDC]	125A/150VDC
Output fuse type	Fast Semiconductor fuse

## PROPERTIES

Ingress protection	IP21
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	A24
Certifications	CE
Cloud connection	No
User interface	LED
Charging Curve Set	10-04,06,18 & 20-10
I/O-cards	Optional
Reporting	No
Radio communication	No

## CHARGER DIMENSIONS

Weight excl. cables [kg]	9
Charger dimensions [mm]	338x335x239

## SHIPPING DIMENSIONS

Box dimensions [mm]

350x380x530

Shipping Weight [kg]

14

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.*