

## TECHNICAL DATA

# MICROPOWER SQ70 PB 48V/130A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	SN4489
Model	Micropower SQ70
Type	48V/130A

### MAINS DATA (50/60HZ)

Output Voltage [V]	48
Output Current [A]	130
Number of phases	3
Rated Voltage range [V]	380-440
Current at nominal voltage [A]	12
Recommended supply fuse [A]	16
Supply cable area	4x2,5 mm <sup>2</sup>
Supply cable length [m]	2,5
Typical Supply Connector	CEE16
Output cable cross-section	50 mm <sup>2</sup>

### BATTERY CONNECTION

Output cable cross-section	50 mm <sup>2</sup>
Output cable terminals (in unit)	M6
Output cable length [m]	3
Typical Output connector	DIN160
Output Voltage [V]	48

### ELECTRIC DATA

Standby Power Consumption [W]	<2,5
Power Consumption [W]	7903
Apparent Power Consumption [VA]	8276

Power Factor	0,96
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	96

## PROPERTIES

Ingress protection	IP21
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	A24
Certifications	CE
HMI	LED
HMI Language	-
Reporting	No
Radio Communication	No
Charging Curve Set	10-04,06,18 & 20-21
I/O-cards	Optional
CE	Yes
UL	No

## CHARGING TIMES

6 Hours cap.ah/5h	746
8 Hours cap.ah/5h	1083
10 Hours cap.ah/5h	1446
12 Hours cap.ah/5h	1735

## CHARGER DIMENSIONS

Weight excl. cables [kg]	8
Weight incl. cables [kg]	12
Outer Dimensions Height [mm]	338

Outer Dimensions Width [mm]	335
Outer Dimensions Depth [mm]	239
Min Spacing Required	User Manual

## SHIPPING DIMENSIONS

Shipping Weight [kg]	15
Box Height [mm]	350
Box Width [mm]	380
Box Depth [mm]	530

## CHARGING

Charging Ionic	
Charging Standard	
Charging Gel	
Charging Li-Ion	
Charging AGM	
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.