

TECHNICAL DATA

MICROPOWER SL180 PB 48V/320A BATTERY CHARGERS

CTATED DATA	VCCUBUING TO) MICROPOWER	CLVNUVDU
2141ED DATA	AUUUNUING H	JWIIGKUPUWEK	STANDARD

Family	Micropower SL180
DC Rating	48V/320A
Part number	DB4789
Model code	1A5B203
Part status	Released
SUPPLY	
Number of phases	3
Rated Voltage range [V]	380-440
Nominal Voltage [V]	400
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	29,7
Current at min rated voltage [A]	31,1
Current at max rated voltage [A]	27
Recommended supply fuse class	C
Recommended RCCB class	В
Supply cable area	4x6 mm2
Supply cable length [m]	?2,5
Typical Supply Connector	CEE32
Standby Power Consumption [W]	<3,5
Power Consumption [W]	19638
Apparent Power Consumption [VA]	20542
Power Factor	0,96
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	95

Printout date: 2025-10-30

OUTPUT DATA	
Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	48
Output Current [A]	320
Output cable cross-section	4/0 AWG
Output cable length [m]	3
Output cable terminals (in unit)	M8
Typical Output connector	DIN320
Output fuse, rating [A/VDC]	2x200A/150VDC
Output fuse type	Fast Semiconductor fuse
PROPERTIES	
Ingress protection	IP21
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	B2
Certifications	CE
Cloud connection	Yes
User interface	LED/Display
Charging Curve Set	Multiple Lead
I/O-cards	Remote Start/Stop
Reporting	Yes
Radio communication	Yes
CHARGER DIMENSIONS	
Weight excl. cables [kg]	42
Charger dimensions [mm]	410x533x515

SHIPPING DIMENSIONS

560x800x600

Shipping Weight [kg]

Box dimensions [mm]

64