

TECHNICAL DATA

MICROPOWER SX17 PB 24V/60A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

| | |
|-------------|-----------------|
| Part number | WK2340 |
| Model | Micropower SX17 |
| Type | 24V/60A |

MAINS DATA (50/60HZ)

| | |
|--------------------------------|------------------------|
| Output Voltage [V] | 24 |
| Output Current [A] | 60 |
| Number of phases | 1 |
| Rated Voltage range [V] | 220-240 |
| Current at nominal voltage [A] | 8,6 |
| Recommended supply fuse [A] | 10 |
| Supply cable area | 3x1,5 mm ² |
| Supply cable length [m] | 2,3 |
| Typical Supply Connector | Fixed or IEC C19/CEE17 |
| Output cable cross-section | 16 mm ² |

BATTERY CONNECTION

| | |
|----------------------------------|--------------------|
| Output cable cross-section | 16 mm ² |
| Output cable terminals (in unit) | M6 |
| Output cable length [m] | 3 |
| Typical Output connector | DIN80 |
| Output Voltage [V] | 24 |

ELECTRIC DATA

| | |
|---------------------------------|------|
| Standby Power Consumption [W] | <5 |
| Power Consumption [W] | 1942 |
| Apparent Power Consumption [VA] | 1982 |

| | |
|--|------|
| Power Factor | 0,98 |
| Inrush current, do not tripp fuse of class [A] | B |
| Output Ripple | <5 |
| Efficiency (at rated power and no cables) [%] | 91 |

PROPERTIES

| | |
|--|------------------------|
| Ingress protection | IP20 |
| Ambient temperature range (at full output power) [deg C] | -5 to +40 |
| Ambient max temp (with reduced output power) [deg C] | 55 |
| Cooling | Convection |
| Short Circuit Protection | Yes |
| Wrong Polarity Protection | Fuse |
| Cabinet Type | A51 |
| Certifications | CE |
| HMI | LED/Display |
| HMI Language | SV / EN / ES / PT / DE |
| Reporting | Yes |
| Radio Communication | Yes |
| Charging Curve Set | Multiple Lead |
| I/O-cards | Basic |
| CE | Yes |
| UL | No |

CHARGING TIMES

| | |
|--------------------|-----|
| 6 Hours cap.ah/5h | 345 |
| 8 Hours cap.ah/5h | 500 |
| 10 Hours cap.ah/5h | 665 |
| 12 Hours cap.ah/5h | |

CHARGER DIMENSIONS

| | |
|------------------------------|-----|
| Weight excl. cables [kg] | 6 |
| Weight incl. cables [kg] | 8 |
| Outer Dimensions Height [mm] | 455 |

| | |
|-----------------------------|-----------------|
| Outer Dimensions Width [mm] | 220 |
| Outer Dimensions Depth [mm] | 103 |
| Min Spacing Required | See User Manual |

SHIPPING DIMENSIONS

| | |
|----------------------|-----|
| Shipping Weight [kg] | 9 |
| Box Height [mm] | 165 |
| Box Width [mm] | 265 |
| Box Depth [mm] | 595 |

CHARGING

| | |
|---------------------|----------|
| Charging Ionic | LK-10-04 |
| Charging Standard | |
| Charging Gel | |
| Charging Li-Ion | |
| Charging AGM | |
| Moisture Resistance | No |
| Dusty Environment | No |
| Outdoor use | No |
| Cold store | No |
| Tropical | No |

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.