

TECHNICAL DATA

MICROPOWER SL150 PB 48V/260A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

| | |
|-------------|------------------|
| Part number | DB4726 |
| Model | Micropower SL150 |
| Type | 48V/260A |

MAINS DATA (50/60HZ)

| |
|--------------------------------|
| Output Voltage [V] |
| Output Current [A] |
| Number of phases |
| Rated Voltage range [V] |
| Current at nominal voltage [A] |
| Recommended supply fuse [A] |
| Supply cable area |
| Supply cable length [m] |
| Typical Supply Connector |
| Output cable cross-section |

BATTERY CONNECTION

| |
|----------------------------------|
| Output cable cross-section |
| Output cable terminals (in unit) |
| Output cable length [m] |
| Typical Output connector |
| Output Voltage [V] |

ELECTRIC DATA

| |
|---------------------------------|
| Standby Power Consumption [W] |
| Power Consumption [W] |
| Apparent Power Consumption [VA] |

Power Factor

Inrush current, do not tripp fuse of class [A]

Output Ripple

Efficiency (at rated power and no cables) [%]

PROPERTIES

Ingress protection

Ambient temperature range (at full output power) [deg C]

Ambient max temp (with reduced output power) [deg C]

Cooling

Short Circuit Protection

Wrong Polarity Protection

Cabinet Type

Certifications

HMI

HMI Language

ReportingNo

Radio CommunicationNo

Charging Curve Set

I/O-cards

CENo

ULNo

CHARGING TIMES

6 Hours cap.ah/5h

8 Hours cap.ah/5h

10 Hours cap.ah/5h

12 Hours cap.ah/5h

CHARGER DIMENSIONS

Weight excl. cables [kg]

Weight incl. cables [kg]

Outer Dimensions Height [mm]

Outer Dimensions Width [mm]

Outer Dimensions Depth [mm]

Min Spacing Required

SHIPPING DIMENSIONS

Shipping Weight [kg]

Box Height [mm]

Box Width [mm]

Box Depth [mm]

CHARGING

Charging Ionic

Charging Standard

Charging Gel

Charging Li-Ion

Charging AGM

Moisture Resistance No

Dusty Environment No

Outdoor use No

Cold store No

Tropical No