

TECHNICAL DATA

MICROPOWER SL370 PB 80V/390A BATTERY CHARGERS

CTATED DATA	VOUDDING	TO MICDODOMED	CTANDADD
2141FIJ IJATA	AGGURIJING	TO MICROPOWER	STANIJAKIJ

Family	Micropower SL370
DC Rating	80V/390A
Part number	DE6859
Model code	1A5B425
Part status	Released
SUPPLY	
Number of phases	3
Rated Voltage range [V]	380-440
Nominal Voltage [V]	400
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	59,4
Current at min rated voltage [A]	62,1
Current at max rated voltage [A]	54
Recommended supply fuse class	C
Recommended RCCB class	В
Supply cable area	4x16 mm2
Supply cable length [m]	?2,5
Typical Supply Connector	CEE63
Standby Power Consumption [W]	<3,5
Power Consumption [W]	39361
Apparent Power Consumption [VA]	41129
Power Factor	0,96
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	96

Printout date: 2025-11-05

OUTPUT DATA	
Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	80
Output Current [A]	390
Output cable cross-section	70(x2) mm2
Output cable length [m]	3
Output cable terminals (in unit)	M8
Typical Output connector	2xDIN320
Output fuse, rating [A/VDC]	3x150A/150VDC
Output fuse type	Fast Semiconductor fuse
PROPERTIES	
Ingress protection	IP21
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	B4
Certifications	CE
Cloud connection	Yes
User interface	LED/Display
Charging Curve Set	Multiple Lead
1/0-cards	Remote Start/Stop
Reporting	Yes
Radio communication	Yes
CHARGER DIMENSIONS	
	04
Weight excl. cables [kg]	64

SHIPPING DIMENSIONS

Box dimensions [mm]	845x800x600
Shipping Weight [kg]	90