

TECHNICAL DATA

MICROPOWER SL190 PB 48V/330A BATTERY CHARGERS

CTATED DATA	VCCUBUING	TO MICROPOWER	CLVNUVDU
2141ED DATA	AGGURDING	TO MIGROPOWER	9 I ANDARD

Family	Micropower SL190
DC Rating	48V/330A
Part number	DB4796
Model code	1A5B2FK
Part status	Released
SUPPLY	
Number of phases	3
Rated Voltage range [V]	-
Nominal Voltage [V]	480
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	26.3
Current at min rated voltage [A]	-
Current at max rated voltage [A]	-
Recommended supply fuse class	C
Recommended RCCB class	A
Supply cable area	4xAWG8
Supply cable length [m]	> 2,5
Typical Supply Connector	tbd
Standby Power Consumption [W]	< 10
Power Consumption [W]	20755
Apparent Power Consumption [VA]	21847
Power Factor	0.95
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	93

Printout date: 2025-12-01

OUTPUT DATA	
Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	48
Output Current [A]	330
Output cable cross-section	4/0 AWG
Output cable length [m]	3
Output cable terminals (in unit)	M8
Typical Output connector	-
Output fuse, rating [A/VDC]	2x200A/150VDC
Output fuse type	Fast Semiconductor fuse
PROPERTIES	
Ingress protection	IP21
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	B2
Certifications	UL
Cloud connection	Yes
User interface	LED / Display
Charging Curve Set	Multiple Lead
1/0-cards	Remote Start/Stop
Reporting	Yes
Radio communication	Yes
CHARGER DIMENSIONS	
OTIANULIN DIMENSIONS	
Weight excl. cables [kg]	42

SHIPPING DIMENSIONS

Box dimensions [mm]

560x800x600

Shipping Weight [kg] 64