

# TECHNICAL DATA

## MICROPOWER ST17 PB 24V/60A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	Micropower ST17
DC Rating	24V/60A
Part number	AN2346
Model code	1AA64N1
Part status	Released

SUPPLY	
Number of phases	3
Rated Voltage range [V]	480
Nominal Voltage [V]	480
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	2,4
Current at min rated voltage [A]	2,4
Current at max rated voltage [A]	2,4
Recommended supply fuse class	C
Recommended RCCB class	B
Supply cable area	4xAWG14
Supply cable length [m]	2,5
Typical Supply Connector	L16-20P
Standby Power Consumption [W]	<2,5
Power Consumption [W]	1878
Apparent Power Consumption [VA]	2018
Power Factor	0,93
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	94

## OUTPUT DATA

Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	24
Output Current [A]	60
Output cable cross-section	#4 AWG
Output cable length [m]	3
Output cable terminals (in unit)	M6
Typical Output connector	DIN80
Output fuse, rating [A/VDC]	125A/150VDC
Output fuse type	Fast Semiconductor fuse

## PROPERTIES

Ingress protection	IP21
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	A24
Certifications	CE
Cloud connection	Yes
User interface	LED/Display
Charging Curve Set	Multiple Lead
I/O-cards	Optional
Reporting	Yes
Radio communication	Yes

## CHARGER DIMENSIONS

Weight excl. cables [kg]	8
Charger dimensions [mm]	338x335x239

# SHIPPING DIMENSIONS

Box dimensions [mm]	350x380x530
Shipping Weight [kg]	13

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.