

## TECHNICAL DATA

# ACCESS 50 24V/130A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	ACCESS 50
DC Rating	24V/130A
Part number	AP2489
Model code	1AA6003
Part status	Released

### SUPPLY

Number of phases	3
Rated Voltage range [V]	380-440
Nominal Voltage [V]	400
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	6,3
Current at min rated voltage [A]	6,6
Current at max rated voltage [A]	5,7
Recommended supply fuse class	C
Recommended RCCB class	B
Supply cable area	4x1,5 mm <sup>2</sup>
Supply cable length [m]	2,5
Typical Supply Connector	CEE16
Standby Power Consumption [W]	<5
Power Consumption [W]	4143
Apparent Power Consumption [VA]	4361
Power Factor	0,95
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	92

## OUTPUT DATA

Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	24
Output Current [A]	130
Output cable cross-section	50 mm <sup>2</sup>
Output cable length [m]	3
Output cable terminals (in unit)	M6
Typical Output connector	DIN160
Output fuse, rating [A/VDC]	150A/150VDC
Output fuse type	Fast Semiconductor fuse

## PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	A16
Certifications	CE
Cloud connection	Yes
User interface	LED/Display
Charging Curve Set	Multiple Lead
I/O-cards	Optional
Reporting	Yes
Radio communication	Yes

## CHARGER DIMENSIONS

Weight excl. cables [kg]	6
Charger dimensions [mm]	387x266x152

SHIPPING DIMENSIONS

Box dimensions [mm]	260x325x550
Shipping Weight [kg]	12

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.