

TECHNICAL DATA

LION 100 80V/80A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER S	STANNARD
Family	LION 100
DC Rating	80V/80A
Part number	LS6383
Model code	1AA7718
Part status	Released
SUPPLY	
Number of phases	3
Rated Voltage range [V]	208-240
Nominal Voltage [V]	208
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	24,3
Current at min rated voltage [A]	24,3
Current at max rated voltage [A]	21,1
Recommended supply fuse class	C
Recommended RCCB class	В
Supply cable area	4x4 mm2
Supply cable length [m]	?2,5
Typical Supply Connector	CEE32
Standby Power Consumption [W]	<10
Power Consumption [W]	8306
Apparent Power Consumption [VA]	8743
Power Factor	0,95
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	93

Printout date: 2025-10-29

OUTPUT DATA	
Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	80
Output Current [A]	80
Output cable cross-section	25 mm2
Output cable length [m]	3
Output cable terminals (in unit)	M8
Typical Output connector	DIN80
Output fuse, rating [A/VDC]	100A/150VDC
Output fuse type	Fast Semiconductor fuse
PROPERTIES	
Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	A18
Certifications	CE
Cloud connection	Yes
User interface	LED/Display
Charging Curve Set	Litium Alg or CAN
1/O-cards	CAN/Detect
Reporting	Yes
Radio communication	Yes
CHARGER DIMENSIONS	
Weight excl. cables [kg]	16

SHIPPING DIMENSIONS Box dimensions [mm] 650x370x440 Shipping Weight [kg] 22