

TECHNICAL DATA

LION 100 48V/165A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD	
Family	LION 100
DC Rating	48V/165A
Part number	LT4556
Model code	1AA7802
Part status	Released
SUPPLY	
Number of phases	3
Rated Voltage range [V]	480
Nominal Voltage [V]	480
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	13,1
Current at min rated voltage [A]	13,1
Current at max rated voltage [A]	13,1
Recommended supply fuse class	C
Recommended RCCB class	В
Supply cable area	4xAWG12
Supply cable length [m]	?2,5
Typical Supply Connector	L16-20P
Standby Power Consumption [W]	<10
Power Consumption [W]	10325
Apparent Power Consumption [VA]	10868
Power Factor	0,95
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	93

Printout date: 2025-10-30

OUTPUT DATA	
Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	48
Output Current [A]	165
Output cable cross-section	1/0 AWG
Output cable length [m]	3
Output cable terminals (in unit)	M8
Typical Output connector	DIN320
Output fuse, rating [A/VDC]	200A/150VDC
Output fuse type	Fast Semiconductor fuse
PROPERTIES	
Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	A19
Certifications	UL
Cloud connection	Yes
User interface	LED/Display
Charging Curve Set	Litium Alg or CAN
1/O-cards	CAN/Detect
Reporting	Yes
Radio communication	Yes
CHARGER DIMENSIONS	
	18
Weight excl. cables [kg]	10

SHIPPING DIMENSIONS Box dimensions [mm] 535x315x850 Shipping Weight [kg] 25