

TECHNICAL DATA

LION 50 BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	LP3433
Model	LION 50
Type	36V/105A

MAINS DATA (50/60HZ)

Output Voltage [V]	36
Output Current [A]	105
Number of phases	3
Rated Voltage range [V]	200-240
Current at nominal voltage [A]	13,9
Recommended supply fuse [A]	16
Supply cable area	4x2,5
Supply cable length [m]	3
Typical Supply Connector	Not included
Output cable cross-section	2x35

BATTERY CONNECTION

Output cable cross-section	2x35
Output cable terminals (in unit)	M6
Output cable length [m]	3
Typical Output connector	User defined
Output Voltage [V]	36

ELECTRIC DATA

Standby Power Consumption [W]	< 5
Power Consumption [W]	4757
Apparent Power Consumption [VA]	5007

Power Factor	0,95
Inrush current, do not tripp fuse of class [A]	Negligible
Output Ripple	< 1
Efficiency (at rated power and no cables) [%]	91

PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Fan
Short Circuit Protection	1
Wrong Polarity Protection	Fuse
Cabinet Type	A16
Certifications	
HMI	LED/Display
HMI Language	SV / EN / ES / PT / DE
Reporting	Yes
Radio Communication	No
Charging Curve Set	N/A
I/O-cards	Yes
CE	Yes
UL	No

CHARGING TIMES

6 Hours cap.ah/5h
8 Hours cap.ah/5h
10 Hours cap.ah/5h
12 Hours cap.ah/5h

CHARGER DIMENSIONS

Weight excl. cables [kg]	
Weight incl. cables [kg]	
Outer Dimensions Height [mm]	387

Outer Dimensions Width [mm]	266
Outer Dimensions Depth [mm]	152
Min Spacing Required	100

SHIPPING DIMENSIONS

Shipping Weight [kg]	11
Box Height [mm]	550
Box Width [mm]	330
Box Depth [mm]	260

CHARGING

Charging Ionic	0
Charging Standard	0
Charging Gel	0
Charging Li-Ion	0
Charging AGM	0
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.