

TECHNICAL DATA

LION 50 36V/105A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD		
Part number	LP3436	
Model	LION 50	
Туре	36V/105A	
MAINS DATA (50/60HZ)		
Output Voltage [V]	36	
Output Current [A]	105	
Number of phases	3	
Rated Voltage range [V]	-	
Current at nominal voltage [A]	6.3	
Recommended supply fuse [A]	10	
Supply cable area	4xAWG14	
Supply cable length [m]	3	
Typical Supply Connector	L16-20P	
Output cable cross-section	#2 AWG	
BATTERY CONNECTION		
Output cable cross-section	#2 AWG	
Output cable terminals (in unit)	M6	
Output cable length [m]	3	
Typical Output connector	DIN160	
Output Voltage [V]	36	
ELECTRIC DATA		
Standby Power Consumption [W]	< 5	
Power Consumption [W]	4937	
Apparent Power Consumption [VA]	5197	

Printout date: 2025-04-28

Power Factor	0.95
Inrush current, do not tripp fuse of class [A]	В
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	93
PROPERTIES	
Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	A16
Certifications	UL
НМІ	LED/Display
HMI Language	SV / EN / ES / PT / DE
Reporting	Yes
Radio Communication	No
Charging Curve Set	N/A
1/O-cards	Yes
CE	No
UL	Yes
CHARGING TIMES	
6 Hours cap.ah/5h	
8 Hours cap.ah/5h	
10 Hours cap.ah/5h	
12 Hours cap.ah/5h	
CHARGER DIMENSIONS	
Weight excl. cables [kg]	7
Weight incl. cables [kg]	10
Outer Dimensions Height [mm]	387

Outer Dimensions Width [mm]	266
Outer Dimensions Depth [mm]	152
Min Spacing Required	Se User Manual
SHIPPING DIMENSIONS	
Shipping Weight [kg]	11
Box Height [mm]	260
Box Width [mm]	325
Box Depth [mm]	550
CHARGING	
Charging Ionic	0
Charging Standard	0
Charging Gel	0
Charging Li-lon	0
Charging AGM	0
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No