

TECHNICAL DATA

LION 30 48V/40A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER S	STANDARD
Family	LION 30
DC Rating	48V/40A
Part number	LH4300
Model code	3AC4503
Part status	Released
SUPPLY	
Number of phases	1
Rated Voltage range [V]	220-240
Nominal Voltage [V]	230
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	10
Current at min rated voltage [A]	10
Current at max rated voltage [A]	10
Recommended supply fuse class	C
Recommended RCCB class	A
Supply cable area	3x1,5 mm2
Supply cable length [m]	2,5
Typical Supply Connector	16A Schuko
Standby Power Consumption [W]	<5
Power Consumption [W]	2275
Apparent Power Consumption [VA]	2298
Power Factor	0,99
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	92

Printout date: 2025-11-23

OUTPUT DATA	
Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	48
Output Current [A]	40
Output cable cross-section	10 mm2
Output cable length [m]	3
Output cable terminals (in unit)	M6
Typical Output connector	DIN80
Output fuse, rating [A/VDC]	80A/150VDC
Output fuse type	Fast Semiconductor fuse
PROPERTIES	
Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	A28
Certifications	CE
Cloud connection	Yes
User interface	LED/Display
Charging Curve Set	Litium Alg or CAN
I/O-cards	CAN/Detect
Reporting	Yes
Radio communication	Yes
CHARGER DIMENSIONS	
Weight excl. cables [kg]	5
Charger dimensions [mm]	456x255x84

185x320x610

8

SHIPPING DIMENSIONS

Shipping Weight [kg]

Box dimensions [mm]