

TECHNICAL DATA

SHARP 80 80V/60A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD		
Family	SHARP 80	
DC Rating	80V/60A	
Part number	SM6349	
Model code	1AB6011	
Part status	Released	
SUPPLY		
Number of phases	3	
Rated Voltage range [V]	380-440	
Nominal Voltage [V]	400	
Rated frequency [Hz]	50-60	
Current at nominal voltage [A]	9,3	
Current at min rated voltage [A]	9,8	
Current at max rated voltage [A]	8,4	
Recommended supply fuse class	C	
Recommended RCCB class	В	
Supply cable area	4x1,5 mm2	
Supply cable length [m]	?2,5	
Typical Supply Connector	CEE16	
Standby Power Consumption [W]	<5	
Power Consumption [W]	6105	
Apparent Power Consumption [VA]	6426	
Power Factor	0,95	
Leakage current [mA]	<3,5	
Efficiency (at rated power and no cables) [%]	95	

Printout date: 2025-11-24

OUTPUT DATA	
Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	80
Output Current [A]	60
Output cable cross-section	16 mm2
Output cable length [m]	3
Output cable terminals (in unit)	M6
Typical Output connector	DIN80
Output fuse, rating [A/VDC]	80A/150VDC
Output fuse type	Fast Semiconductor fuse
PROPERTIES	
Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	\$16
Certifications	CE
Cloud connection	No
User interface	LED
Charging Curve Set	10-04,06,18 & 20-09
I/O-cards	No
Reporting	No
Radio communication	No
CHARGER DIMENSIONS	
Weight excl. cables [kg]	6
Charger dimensions [mm]	387x266x152

SHIPPING DIMENSIONS

Box dimensions [mm]	260x325x550
Shipping Weight [kg]	10