

TECHNICAL DATA

SHARP 100 48V/130A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD	
Family	SHARP 100
DC Rating	48V/130A
Part number	SS4484
Model code	1AB7712
Part status	Released
SUPPLY	
Number of phases	3
Rated Voltage range [V]	440-440
Nominal Voltage [V]	440
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	11,2
Current at min rated voltage [A]	11,2
Current at max rated voltage [A]	11,2
Recommended supply fuse class	C
Recommended RCCB class	В
Supply cable area	4x2,5 mm2
Supply cable length [m]	?2,5
Typical Supply Connector	CEE16
Standby Power Consumption [W]	<10
Power Consumption [W]	8124
Apparent Power Consumption [VA]	8552
Power Factor	0,95
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	93

Printout date: 2025-12-01

OUTPUT DATA	
Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	48
Output Current [A]	130
Output cable cross-section	50 mm2
Output cable length [m]	3
Output cable terminals (in unit)	M8
Typical Output connector	DIN160
Output fuse, rating [A/VDC]	150A/150VDC
Output fuse type	Fast Semiconductor fuse
PROPERTIES	
Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	\$18
Certifications	CE
Cloud connection	No
User interface	LED
Charging Curve Set	10-04,06,18 & 20-09
1/O-cards	No
Reporting	No
Radio communication	No
CHARGER DIMENSIONS	
Weight excl. cables [kg]	16

SHIPPING DIMENSIONS Box dimensions [mm] 650x370x440

23

Shipping Weight [kg]