

## TECHNICAL DATA

# SHARP 100 80V/100A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	SS6424
Model	SHARP 100
Type	80V/100A

#### MAINS DATA (50/60HZ)

Output Voltage [V]	80
Output Current [A]	100
Number of phases	3
Rated Voltage range [V]	440-440
Current at nominal voltage [A]	14.1
Recommended supply fuse [A]	16
Supply cable area	4x2,5 mm <sup>2</sup>
Supply cable length [m]	3
Typical Supply Connector	CEE16
Output cable cross-section	35 mm <sup>2</sup>

#### BATTERY CONNECTION

Output cable cross-section	35 mm <sup>2</sup>
Output cable terminals (in unit)	M8
Output cable length [m]	3
Typical Output connector	DIN160
Output Voltage [V]	80

#### ELECTRIC DATA

Standby Power Consumption [W]	<10
Power Consumption [W]	10265
Apparent Power Consumption [VA]	10806

Power Factor	0,95
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	94

## PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	S18
Certifications	CE
HMI	LED
HMI Language	-
Reporting	No
Radio Communication	No
Charging Curve Set	10-04,06,18 & 20-09
I/O-cards	No
CE	Yes
UL	No

## CHARGING TIMES

6 Hours cap.ah/5h	574
8 Hours cap.ah/5h	833
10 Hours cap.ah/5h	1112
12 Hours cap.ah/5h	1334

## CHARGER DIMENSIONS

Weight excl. cables [kg]	16.1
Weight incl. cables [kg]	19.4
Outer Dimensions Height [mm]	529

Outer Dimensions Width [mm]	256
Outer Dimensions Depth [mm]	243
Min Spacing Required	See User Manual

## SHIPPING DIMENSIONS

Shipping Weight [kg]	21.9
Box Height [mm]	410
Box Width [mm]	365
Box Depth [mm]	525

## CHARGING

Charging Ionic	LK10-18 Ionic mixture
Charging Standard	LK10-06 Standard Curve
Charging Gel	LK20-09
Charging Li-Ion	0
Charging AGM	LK20-09
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.*