

TECHNICAL DATA

ACCESS 100 BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER	STANDARD
Part number	AS2621
Model	ACCESS 100
Туре	24V/200A
MAINS DATA (50/60HZ)	
Output Voltage [V]	24
Output Current [A]	200
Number of phases	3
Rated Voltage range [V]	380-415
Current at nominal voltage [A]	9,8
Recommended supply fuse [A]	10
Supply cable area	4x1,5
Supply cable length [m]	3,0
Typical Supply Connector	CEE16
Output cable cross-section	2x70
BATTERY CONNECTION	
Output cable cross-section	2x70
Output cable terminals (in unit)	M8
Output cable length [m]	3,0
Typical Output connector	User defined
Output Voltage [V]	24
ELECTRIC DATA	
Standby Power Consumption [W]	<10
Power Consumption [W]	6462
Apparent Power Consumption [VA]	6802

Printout date: 2025-12-01

Power Factor	0,95
Inrush current, do not tripp fuse of class [A]	Neglible
Output Ripple	<1
Efficiency (at rated power and no cables) [%]	91
PROPERTIES	
Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Fan
Short Circuit Protection	1
Wrong Polarity Protection	Fuse
Cabinet Type	A18
Certifications	CE
НМІ	LED/Display
HMI Language	SC/ EN / DE / ES / PT
Reporting	Yes
Radio Communication	Yes
Charging Curve Set	Multiple
I/O-cards	Optional
CE	Yes
UL	No
CHARGING TIMES	
6 Hours cap.ah/5h	
8 Hours cap.ah/5h	1665
10 Hours cap.ah/5h	2221
12 Hours cap.ah/5h	2665
CHARGER DIMENSIONS	
Weight excl. cables [kg]	16.1
Weight incl. cables [kg]	23.2
Outer Dimensions Height [mm]	529

Outer Dimensions Width [mm]	256
Outer Dimensions Depth [mm]	243
Min Spacing Required	300
SHIPPING DIMENSIONS	
Shipping Weight [kg]	25.6
Box Height [mm]	440
Box Width [mm]	370
Box Depth [mm]	650
CHARGING	
Charging Ionic	LK10-18 Ionic mixture
Charging Standard	LK10-06 Standard Curve
Charging Gel	LK20-09
Charging Li-lon	0
Charging AGM	LK20-09
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No